



Mr Fixx

BATH FIX

Acrylic Co-polymer Waterproofing



Flexible
Waterproofing



Easy To
Apply



Terrace/Roof
Waterproofing



Higher
Elongation



BATH FIX | Waterproofing | 15 Kgs

Product Description :-

Bath Fix is a high-performance two-component waterproofing coating designed for extreme wet zones such as bathrooms, toilets, balconies, and terraces. It combines a specially formulated polymer dispersion (Part A) with high-grade cementitious powder (Part B) to form a tough, elastic, and seamless membrane that defends against water, cracks, and weathering.

Packing :-

✓ 15 kg Set (Part A – 5 kg | Part B – 10 kg)

Health & Safety

Precautions :-



Special Features & Advantages :-

- ✓ Super Stretch Power – With elongation up to 80%, BATH FIX expands with your surface to prevent cracking and leaking.
- ✓ Seamless & Joint-Free Shield – Forms a continuous waterproofing skin – no joints, no chance for water to sneak through.
- ✓ Bonding That Lasts – Strong adhesion to old and new concrete – locks in protection even under tile beds.
- ✓ Brush-On Ease, Worker Friendly – Just mix and apply – no complicated tools, no contractor complaints.
- ✓ Ideal for Bathrooms & Wet Zones – Custom-made for wet, tricky areas like toilets, sunken slabs & showers.
- ✓ Eco-Safe & Non-Toxic – Zero VOC – safe for applicators and homeowners.
- ✓ Crack-Bridging Beast – Bridges cracks up to 1.2 mm with ease, reducing leak paths.

Technical Properties :-

Testing Parameters	Results
Appearance	Part A: Milky White / Part B: Grey Powder
Mixing Ratio (A:B by weight)	1 : 2
Mixing Time	2–3 minutes using a drill (350–400 RPM)
Pot Life @ 27°C	Approx. 1 Hour
Re-coat Interval	6–8 hours @ 30°C
Full Cure	7 Days
Foot Traffic	After 48 Hours
Crack Bridging	Up to 1.2 mm
Elongation (28 days @ 30°C)	~80%
Tensile Strength (28 days @ 30°C)	1.0 – 1.2 N/mm ²
Water Penetration Resistance	≥ 1.5 Bar
VOC Content	< 0.5 gm/litre
Shore A Hardness	Approx. 90
Application Temp. Range	+5°C to +42°C
Service Temperature	-10°C to +45°C

Application :-

- ✓ Toilets & Bathrooms – On slab, walls, behind tiles – total zone protection.
- ✓ Sunken Slabs & Wet Shafts – Ensures peace of mind in under-tile and under-plaster applications.
- ✓ Balconies & Chajjas – Withstands water, sun, and temperature changes.
- ✓ Terraces & Mild Traffic Zones – Durable under foot traffic & rain.
- ✓ Water Tanks, Pools, & Drains – For internal water retaining surfaces.
- ✓ Basements & Concrete Walls – Works against rising damp and lateral water ingress.

Coverage :-

- ✓ Approx. 1.2kg/m²/mm thickness coat.
(minimum 2 coat required)
- ✓ Typical usage: 2 – 2.5 kg/m² for 2 coats.

Contact Us – info.mrfixx@gmail.com

Marketed By : Kitpot Private Limited
A-202, Bellacasa Apartment, Althan Canal Road,
Althan, Surat, Gujarat, India – 395017.

MRP :- ₹5,350/- (Incl. of all taxes)

G.S.T :- 18%

Batch No. :-

Mfd Dt. :-

Expiry Dt. :-

Manufactured By : Astone Chemical Industry, Mankna, Surat – 394325.

Storage :-

Cool, dry place; protect from frost & heat.

Shelf Life :-

12 months from date of manufacturing.

