



Mr Fixx

SUPER FIX COAT

High-Performance Two-Component
Crack-Bridging Waterproof Coating



Flexible
Waterproofing



Easy To
Apply



Terrace/Roof
Waterproofing



Waterproofing



Higher
Elongation



GERMAN
POLYMERS



SUPER FIX COAT | Waterproofing | 15 Kgs

Product Description :-

Super Fixx Coat is an elastomeric, two-component, cementitious acrylic polymer-based waterproof coating designed to fight water under even the harshest conditions. Engineered for extreme pressure, high flexibility, and aggressive environments, this product bridges cracks, resists water up to 7 bar pressure, and protects against chemical, UV, and chloride attack.

Packing :-

✓ 15 kg (Composite Pack – Powder + Liquid)

Health & Safety

Precautions :-



Special Features & Advantages :-

- ✓ 7-Bar Water Pressure Resistance – Capable of withstanding pressurized water zones – even underground!
- ✓ Highly Flexible Membrane – Bridges existing and future cracks with elongation >80%.
- ✓ Self-Priming on Wet Surfaces – Bonds effortlessly – even in SSD damp conditions.
- ✓ Rainproof in 3–5 Hours – Fast-cure technology = less downtime, faster project delivery
- ✓ Concrete Armor – Shields concrete from acid gases, CO_2 , chloride attack, and carbonation.
- ✓ Zero VOC & Potable Water Safe – Safe for environment, humans, and water tanks.
- ✓ UV & Freeze–Thaw Resistant – Built to handle sun, snow, or sludge – no matter the weather.

Technical Properties :-

Testing Parameters	Results
Appearance	Part A: Milky White, Part B: Grey Powder
Mixing Ratio (A:B by weight)	10kg Powder : 5 kg Liquid (Approx.2:1)
Mixing Time	2–3 minutes (slow-speed mixer)
Pot Life @ 27°C	~30 minutes
Application Temp.	+5°C to +30°C
Service Temp.	0°C to +50°C
Crack Bridging	Excellent (>1 mm dynamic cracks)
Shore A Hardness	Approx. 70
Tensile Strength (28 days @ 23°C)	>0.5 N/mm ²
Elongation @ 28 Days (Grey)	>120%
Water Pressure Resistance	Upto 7 bar (+ve pressure)
Vapor Diffusion Resistance	Approx. 1000 μ
VOC	Zero

Manufactured By : Astone Chemical Industry, Mankna, Surat – 394325.

Storage :-

Store in dry, cool place away from heat & moisture.

Shelf Life :-

24 months (sealed condition) | Consume opened packs immediately.

Application :-

- ✓ Toilets, Bathrooms, & Wet Rooms.
- ✓ Terraces, Podiums & Balconies.
- ✓ Underground Basements & Precast Garages.
- ✓ Swimming Pools, Water Tanks, Water Bodies.
- ✓ Concrete Roofs & Ducts.
- ✓ Industrial Plants (resistant to acids, salts, chloride).
- ✓ Masonry Walls under Pressure Water Conditions.
- ✓ As a crack-bridging base coat under tiles/plaster.

Coverage :-

- ✓ 2.0–2.5 kg/m² for 2 coats at 1 mm DFT.
- ✓ Actual coverage depends on surface roughness & site conditions.

Contact Us – info.mrfixx@gmail.com

Marketed By : Kitpot Private Limited
A-202, Bellacasa Apartment, Althan Canal Road,
Althan, Surat, Gujarat, India – 395017.

MRP :- ₹5,350/- (Incl. of all taxes)

G.S.T :- 18%

Batch No. :-

Mfd Dt. :-

Expiry Dt. :-

